

Serial Number: 10/648,807
Attorney/Docket No.: KEIT3001/FJD

15-18
19
20

List of Current Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1-10 (canceled).

11. (New) A method for determining a mass flow rate of a fluid flowing in a pipe, comprising the step of:

(1)
(19)
producing vortices, especially Karman vortices, in the flowing fluid by means of a bluff body around which the fluid flows, the bluff body having at least two separation edges, and determining a repetition frequency with which the vortices are produced;

producing, on the basis of the determined repetition frequency, a flow rate measurement value, which represents a volume flow rate or a flow velocity;

(20)
local registering of a first pressure, p_1 , acting in the flowing fluid at a first measurement point, which is located, with reference to the flow direction, by the two separation edges of the bluff body or downstream from at least one of the separation edges; and

(22)
local registering of a second pressure, p_2 , acting in the flowing fluid at a second measurement point separated from the first measurement point in the flow direction, whereas:

by action of the generated vortices, at least one of the registered pressures p_1 , and p_2 changes periodically at least with the repetition frequency, using the registered first pressure, p_1 , a pressure measurement value that is produced which represents an average dynamic pressure acting, averaged over time, at least partly in the flow direction, as well as using the pressure measurement value and the flow rate

12/18/03
12/26/03
12/27/03

(col 8, lines 56-59)

measurement value, a mass flow rate measurement value is produced representing the mass flow. (col 3, lines 14 - 44)

12. (New) The method as claimed in claim 10, wherein:

the repetition frequency, with which the vortices are produced, is determined on the basis of at least one of the registered pressures p_1 , p_2 . (col 3, lines 14-44)

13. (New) The method as claimed in claim 10, wherein:

at least one of the measurement points is arranged at the bluff body or inside of the same. (fig. 1)

14. (New) The method as claimed in claim 10, wherein:

a pressure difference between the two locally registered pressures is determined for producing the pressure measurement value. ~~col. 1, lines~~

15

15. (New) The method as claimed in claim 13, wherein:

a differential pressure sensor, especially one arranged within the bluff body, is exposed, especially simultaneously, to the first and second pressures, p_1 , p_2 , for registering the pressure difference.

16. (New) The method as claimed in claim 14, wherein:

Serial Number: 10/648,807

Attorney/Docket No.: KEIT3001/FJD

a pressure difference signal is derived from the locally registered pressures, p_1 , p_2 , to represent the pressure difference.

17. (New) The method as claimed in claim 16, wherein:

the pressure difference signal is digitized for producing the pressure measurement value.

18. (New) The method as claimed in claim 16, wherein:

the pressure measurement value and/or flow rate measurement value is/are determined on the basis of a spectral analysis, especially a digital spectral analysis, of the pressure difference signal.

col 3 lines 14-44
19. (New) The method as claimed in claim 11, wherein:

one of the locally registered pressures p_1 , p_2 is a total pressure acting in the flow direction and/or a static pressure acting in the fluid.

20. (New) The method as claimed in claim 11, where:

a sensor element in the form of an oscillating body arranged within, or downstream from, the bluff body is used for determining the pressure difference.